

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : A-Clean 305
Revision date : 04-11-2019
Print date : 08-11-2019

Version (Revision) : 6.0.0

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

A-Clean 305

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

PC 35 - Washing and cleaning products

Sector of uses [SU]

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Process categories [PROC]

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 11 - Non industrial spraying

PROC 19 - Manual activities involving hand contact

Environmental release categories [ERC]

ERC 8a - Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

Uses advised against

This product should not be used for purposes other than the applications referred to above.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Christeyns (Qlean-tec BV)

Street : Lireweg 12

Postal code/city : 2153 PH Nieuw-Vennep

Telephone : +31 (0)297-274390

Telefax : +31 (0)297-272442

Information contact : SHE Department

Website : www.qleantec.com

E-mail (competent person) : marketing@qleantec.com

1.4 Emergency telephone number

Only for the purpose of informing medical personnel in case of acute intoxication:

The Netherlands: NVIC 030 - 274 88 88

Belgium: Antigifcentrum : 070 – 245 245

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Skin Corr. 1A ; H314 - Skin corrosion/irritation : Category 1A ; Causes severe skin burns and eye damage.

Eye Dam. 1 ; H318 - Serious eye damage/eye irritation : Category 1 ; Causes serious eye damage.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Corrosion (GHS05)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : A-Clean 305
Revision date : 04-11-2019
Print date : 08-11-2019

Version (Revision) : 6.0.0

Signal word

Danger

Hazard components for labelling

POTASSIUM HYDROXIDE ; CAS No. : 1310-58-3
SODIUM HYDROXIDE ; CAS No. : 1310-73-2
SODIUMMETASILICATE ; CAS No. : 10213-79-3
ALCOHOLS, C12-14, ETHOXYLATED ; CAS No. : 68439-50-9

Hazard statements

H314 Causes severe skin burns and eye damage.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P310 Immediately call a POISON CENTER/doctor.
P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

Remark

The product is classified and labelled according to EC directives or corresponding national laws.

2.3 Other hazards

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

2.4 Additional information

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

POTASSIUM HYDROXIDE ; REACH registration No. : 01-2119487136-33 ; EC No. : 215-181-3 ; CAS No. : 1310-58-3
Weight fraction : $\geq 2,5 - < 5 \%$
Classification 1272/2008 [CLP] : Met. Corr. 1 ; H290 Skin Corr. 1A ; H314 Eye Dam. 1 ; H318 Acute Tox. 4 ; H302
SODIUM HYDROXIDE ; REACH registration No. : 01-2119457892-27 ; EC No. : 215-185-5 ; CAS No. : 1310-73-2
Weight fraction : $\geq 2,5 - < 5 \%$
Classification 1272/2008 [CLP] : Met. Corr. 1 ; H290 Skin Corr. 1A ; H314 Eye Dam. 1 ; H318
PROPAN-2-OL ; REACH registration No. : 01-2119457558-25 ; EC No. : 200-661-7 ; CAS No. : 67-63-0
Weight fraction : $< 2,5 \%$
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319 STOT SE 3 ; H336
NATRIUM CUMEENSULFONAAT ; REACH registration No. : 01-2119489411-37 ; EC No. : 248-983-7 ; CAS No. : 28348-53-0
Weight fraction : $< 2,5 \%$
Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319
ALCOHOLS, C12-14, ETHOXYLATED ; REACH registration No. : POLYMER ; CAS No. : 68439-50-9
Weight fraction : $\geq 1 - < 2,5 \%$
Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Aquatic Chronic 3 ; H412
SODIUMMETASILICATE ; REACH registration No. : 01-2119449811-37 ; EC No. : 229-912-9 ; CAS No. : 10213-79-3
Weight fraction : $\geq 1 - < 2,5 \%$
Classification 1272/2008 [CLP] : Met. Corr. 1 ; H290 Skin Corr. 1B ; H314 Eye Dam. 1 ; H318 STOT SE 3 ; H335

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

Trade name : A-Clean 305
Revision date : 04-11-2019
Print date : 08-11-2019

Version (Revision) : 6.0.0

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice.

Following inhalation

No special measures are necessary.

In case of skin contact

Change contaminated, saturated clothing. Wash contaminated clothing prior to re-use.

After eye contact

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Call a physician in any case! Do NOT induce vomiting. If major quantity of dust is swallowed or inhaled, immediately drink: Water

4.2 Most important symptoms and effects, both acute and delayed

The following symptoms may occur: No known symptoms to date.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water mist Foam Extinguishing powder Carbon dioxide (CO₂)

Unsuitable extinguishing media

Full water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon monoxide Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Protective clothing.

5.4 Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Emergency procedures

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Make sure spills can be contained, e.g. in sump pallets or kerbed areas.

6.3 Methods and material for containment and cleaning up

For containment

Collect in closed and suitable containers for disposal. Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Suitable material for taking up: Sand Absorbing material, organic

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : A-Clean 305
Revision date : 04-11-2019
Print date : 08-11-2019

Version (Revision) : 6.0.0

6.4 Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage



7.1 Precautions for safe handling

None

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep/Store only in original container. Suitable container/equipment material: Stainless steel Polyethylene (PE)

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

DNEL/DMEL and PNEC values

DNEL/DMEL

Limit value type :	DNEL Consumer (local) (POTASSIUM HYDROXIDE ; CAS No. : 1310-58-3)
Exposure route :	Inhalation
Exposure frequency :	Long-term (repeated)
Limit value :	1 mg/m ³
Limit value type :	DNEL worker (local) (POTASSIUM HYDROXIDE ; CAS No. : 1310-58-3)
Exposure route :	Inhalation
Exposure frequency :	Long-term (repeated)
Limit value :	1 mg/m ³
Limit value type :	DNEL/DMEL (Consumer) (SODIUM HYDROXIDE ; CAS No. : 1310-73-2)
Exposure route :	Inhalation
Exposure frequency :	Long-term (repeated)
Limit value :	1 mg/m ³
Limit value type :	DNEL/DMEL (Worker) (SODIUM HYDROXIDE ; CAS No. : 1310-73-2)
Exposure route :	Inhalation
Exposure frequency :	Long-term (repeated)
Limit value :	1 mg/m ³
Limit value type :	DNEL Consumer (systemic) (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	319 mg/kg
Limit value type :	DNEL Consumer (systemic) (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	89 mg/m ³
Limit value type :	DNEL Consumer (systemic) (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route :	Oral
Exposure frequency :	Long-term
Limit value :	26 mg/kg
Limit value type :	DNEL worker (systemic) (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route :	Dermal

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : A-Clean 305
Revision date : 04-11-2019
Print date : 08-11-2019

Version (Revision) : 6.0.0

Exposure frequency : Long-term
Limit value : 888 mg/kg
Limit value type : DNEL worker (systemic) (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 500 mg/m³
Limit value type : DNEL Consumer (systemic) (SODIUMMETASILICATE ; CAS No. : 10213-79-3)
Exposure route : Oral
Exposure frequency : Long-term
Limit value : 0,74 mg/kg
Limit value type : DNEL Consumer (systemic) (SODIUMMETASILICATE ; CAS No. : 10213-79-3)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 1,55 mg/m³
Limit value type : DNEL Consumer (systemic) (SODIUMMETASILICATE ; CAS No. : 10213-79-3)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 0,74 mg/kg
Limit value type : DNEL worker (systemic) (SODIUMMETASILICATE ; CAS No. : 10213-79-3)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 6,22 mg/m³
Limit value type : DNEL worker (systemic) (SODIUMMETASILICATE ; CAS No. : 10213-79-3)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 1,49 mg/kg

PNEC
Limit value type : PNEC (Aquatic, freshwater) (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route : Water (Including sewage plant)
Limit value : 140,9 mg/l
Limit value type : PNEC (Aquatic, marine water) (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route : Water (Including sewage plant)
Limit value : 140,9 mg/l
Limit value type : PNEC (Sediment, freshwater) (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route : Soil
Limit value : 552 mg/kg
Limit value type : PNEC (Sediment, marine water) (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route : Soil
Limit value : 552 mg/kg
Limit value type : PNEC (Soil) (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route : Soil
Limit value : 28 mg/kg
Limit value type : PNEC (Sewage treatment plant) (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route : Water (Including sewage plant)
Limit value : 2251 mg/l
Limit value type : PNEC (Aquatic, freshwater) (SODIUMMETASILICATE ; CAS No. : 10213-79-3)
Exposure route : Water (Including sewage plant)
Limit value : 7,5 mg/l
Limit value type : PNEC (Aquatic, marine water) (SODIUMMETASILICATE ; CAS No. : 10213-79-3)
Exposure route : Water (Including sewage plant)
Limit value : 1 mg/l
Limit value type : PNEC (Sewage treatment plant) (SODIUMMETASILICATE ; CAS No. : 10213-79-3)
Exposure route : Water (Including sewage plant)
Limit value : 1000 mg/l

8.2 Exposure controls

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : A-Clean 305
Revision date : 04-11-2019
Print date : 08-11-2019

Version (Revision) : 6.0.0

Personal protection equipment

Skin protection

Hand protection Suitable gloves type EN ISO 374 Butyl caoutchouc (butyl rubber) NBR (Nitrile rubber) Required properties liquid-tight. Breakthrough time (maximum wearing time) Permeation time (maximum wear time) Thickness of the glove material Nitril: 0,12 mm Butyl: 0,50 mm

General health and safety measures

Immediately remove any contaminated clothing, shoes or stockings. Wash contaminated clothing prior to re-use.

Environmental exposure controls

See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Colour : colourless

Odour : odourless

Safety relevant basis data

Physical state :			Liquid
Melting point/melting range :			No data available
Initial boiling point and boiling range :	(1013 hPa)	>	100 °C
Decomposition temperature :		>	200 °C
Freezing point :			No data available
Flash point :			not applicable
Auto-ignition temperature :		>	250 °C
Lower explosion limit :			not applicable
Upper explosion limit :			not applicable
Vapour Pressure :	(20 °C)		No data available
Evaporation rate (n-butylacetate = 1) :			No data available
Density :	(20 °C)	approx.	1,1 g/cm ³
Water solubility :	(20 °C)		100 Wt %
pH :		>	13,5
Partition coefficient (n-octanol/water) :		<	3
Viscosity :	(20 °C)	<	10 mPa.s
Vapour density (air = 1) :	(101 kPa)		No data available
Valt onder Detergentia Verordening (EG) Nr. 648/2004 J/N			yes

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

not applicable

10.2 Chemical stability

Stable under normal conditions of use

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : A-Clean 305
Revision date : 04-11-2019
Print date : 08-11-2019

Version (Revision) : 6.0.0

Strong oxidizers

10.6 Hazardous decomposition products

No information available.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute effects

Acute oral toxicity

Parameter :	LD50 (POTASSIUM HYDROXIDE ; CAS No. : 1310-58-3)
Exposure route :	Oral
Species :	Rat
Effective dose :	365 mg/kg
Parameter :	LD50 (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route :	Oral
Species :	Rat
Effective dose :	5840 mg/kg

Irritant and corrosive effects

Primary irritation to the skin

Not an irritant.

Irritation to eyes

Not an irritant.

Irritation to respiratory tract

No data available

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

This substance does not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Germ cell mutagenicity

No indications of human germ cell mutagenicity exist.

Reproductive toxicity

This substance does not meet the criteria for classification as CMR category 1A or 1B according to CLP.

STOT-single exposure

not applicable

SECTION 12: Ecological information

12.1 Toxicity

harmless to aquatic organisms up to the tested concentration

12.2 Persistence and degradability

Biodegradable.

12.3 Bioaccumulative potential

No indication of bioaccumulation potential.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.6 Other adverse effects

None

12.7 Additional ecotoxicological information

None

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : A-Clean 305
Revision date : 04-11-2019
Print date : 08-11-2019

Version (Revision) : 6.0.0

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Delivery to an approved waste disposal company. Contaminated packages must be completely emptied and can be re-used following proper cleaning. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

14.1 UN number

UN 1760

14.2 UN proper shipping name

Land transport (ADR/RID)

CORROSIVE LIQUID, N.O.S. (POTASSIUM HYDROXIDE · SODIUM HYDROXIDE)

Sea transport (IMDG)

CORROSIVE LIQUID, N.O.S. (POTASSIUM HYDROXIDE · SODIUM HYDROXIDE)

Air transport (ICAO-TI / IATA-DGR)

CORROSIVE LIQUID, N.O.S. (POTASSIUM HYDROXIDE · SODIUM HYDROXIDE)

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 8
Classification code : C9
Hazard identification number (Kemler No.) : 80
Tunnel restriction code : E
Special provisions : LQ 11 · E 2
Hazard label(s) :



8

Sea transport (IMDG)

Class(es) : 8
EmS-No. : F-A / S-B
Special provisions : LQ 11 · E 2 · IMDG-Code segregation group 18 - Alkalis
Hazard label(s) :



8

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 8
Special provisions : E 2
Hazard label(s) :



8

14.4 Packing group

II

14.5 Environmental hazards

Land transport (ADR/RID) : No

Sea transport (IMDG) : No

Air transport (ICAO-TI / IATA-DGR) : No

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : A-Clean 305
Revision date : 04-11-2019
Print date : 08-11-2019

Version (Revision) : 6.0.0

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Restrictions on use

Use restriction according to REACH annex XVII, no. : 3, 40

Other regulations (EU)

Labelling for contents according to regulation (EC) No. 648/2004

anionic surfactants	< 5 %
non-ionic surfactants	< 5 %

15.2 Chemical safety assessment

Chemical safety assessments for substances in this preparation were not carried out.

SECTION 16: Other information

16.1 Indication of changes

02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] - Hazard components for labelling · 03. Hazardous ingredients · 08. Occupational exposure limit values · 14. UN proper shipping name - Land transport (ADR/RID) · 14. UN proper shipping name - Sea transport (IMDG) · 14. UN proper shipping name - Air transport (ICAO-TI / IATA-DGR) · 14. Transport hazard class(es) - Land transport (ADR/RID) · 14. Transport hazard class(es) - Sea transport (IMDG) · 14. Transport hazard class(es) - Air transport (ICAO-TI / IATA-DGR) · 15. Restrictions on use

16.2 Abbreviations and acronyms

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road
ASTM = American Society of Testing and Materials (US)
CAS No = Chemical Abstracts Service Number (see ACS - American Chemical Society)
DNEL = Derived No-Effect Level
DT50 = Time for 50% loss; half-life
EbC50 = Median effective concentration (biomass, e.g. of algae)
EC50 = Median effective concentration
EINECS = European Inventory of Existing Commercial Chemical Substances
ELINCS = European List of Notified (New) Chemicals (see Tab 7, Background - Guide)
ErC50 = Median effective concentration (growth rate, e.g. of algae)
EWC = European Waste Catalogue
IATA = International Air Transport Association
IC50 = Concentration that produces 50% inhibition
IMDG = International Maritime Dangerous Goods Code
IMO = International Maritime Organization
LC50 = Concentration required to kill 50% of test organisms
LD50 = Dose required to kill 50% of test organisms
LEL = Lower Explosive Limit/Lower Explosion Limit
LOAEL = Lowest observed adverse effect level
MRL = Maximum Residue Limit
NOAEL = No Observed Adverse Effect Level
NOEC = No observed effect concentration
NOEL = No Observable Effect Level
OEL = Occupational Exposure Limits
PBT = Persistent, Bioaccumulative or Toxic

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : A-Clean 305
Revision date : 04-11-2019
Print date : 08-11-2019

Version (Revision) : 6.0.0

PNEC = Previsible Non Effect Concentration
STEL = Short-Term Exposure Limit
TWA = Time-Weighted Average
vPvB = Very Persistent and Very Bioaccumulative

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

16.6 Training advice

None

16.7 Additional information

Article No.: 500001042670

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
