

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : A-Clean 518
Revision date : 06-07-2016
Print date : 30-04-2018

Version (Revision) : 5

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

A-Clean 518

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Washing and cleaning products (including solvent based products)

Sector of uses [SU]

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Process categories [PROC]

PROC8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC11 - Non industrial spraying

PROC19 - Hand-mixing with intimate contact and only PPE available

Environmental release categories [ERC]

ERC8a - Wide dispersive indoor use of processing aids in open systems

Uses advised against

This product should not be used for purposes other than the applications referred to above.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Qlean-tec BV

Street : Rendementsweg 24

Postal code/city : 3641 SL Mijdrecht

Telephone : +31 (0)297-274390

Telefax : +31 (0)297-272442

Website : www.qleantec.com

E-mail (competent person) : marketing@qleantec.com

1.4 Emergency telephone number

Qlean-tec: +31 (0) 297 274390 (08:00- 17:00 hours)

Only for the purpose of informing medical personnel in case of acute intoxications:

Netherlands: NVIC +31 (0) 30 2748888

Belgium: Antigifcentrum +32 (0) 70 245245

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Acute Tox. 4 ; H302 - Acute toxicity (oral) : Category 4 ; Harmful if swallowed.

Eye Dam. 1 ; H318 - Serious eye damage/eye irritation : Category 1 ; Causes serious eye damage.

Skin Corr. 1B ; H314 - Skin corrosion/irritation : Category 1B ; Causes severe skin burns and eye damage.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : A-Clean 518
Revision date : 06-07-2016
Print date : 30-04-2018

Version (Revision) : 5

Corrosion (GHS05) · Exclamation mark (GHS07)

Signal word

Danger

Hazard components for labelling

PHOSPHORIC ACID 16 % ; CAS No. : 7664-38-2
ALKYLBENZEENSULFONZUUR ; CAS No. : 85536-14-7
AMMONIUM BIFLUORIDE ; CAS No. : 1341-49-7

Hazard statements

H314 Causes severe skin burns and eye damage.
H302 Harmful if swallowed.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P310 Immediately call a POISON CENTER/doctor/....
P330 Rinse mouth.
P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3 Other hazards

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

2.4 Additional information

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

PHOSPHORIC ACID ; REACH registration No. : 01-2119485924-24 ; EC No. : 231-633-2 ; CAS No. : 7664-38-2
Weight fraction : $\geq 10 - < 25$ %
Classification 1272/2008 [CLP] : Met. Corr. 1 ; H290 Skin Corr. 1B ; H314 Eye Dam. 1 ; H318
ALKYLBENZEENSULFONZUUR ; REACH registration No. : 01-2119490234-40 ; EC No. : 287-494-3 ; CAS No. : 85536-14-7
Weight fraction : $\geq 10 - < 25$ %
Classification 1272/2008 [CLP] : Skin Corr. 1B ; H314 Acute Tox. 4 ; H302
NATRIUM XYLEENSULFONAAT ; REACH registration No. : 01-2119513350-56 ; EC No. : 215-090-9 ; CAS No. : 1300-72-7
Weight fraction : $\geq 2,5 - < 10$ %
Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319 STOT SE 3 ; H335
AMMONIUM BIFLUORIDE ; REACH registration No. : 01-2119489180-38 ; EC No. : 215-676-4 ; CAS No. : 1341-49-7
Weight fraction : $\geq 2,5 - < 10$ %
Classification 1272/2008 [CLP] : Acute Tox. 3 ; H301 Skin Corr. 1B ; H314 Eye Dam. 1 ; H318
1-METHOXY-2-PROPANOL ; REACH registration No. : 01-2119457435-35 ; EC No. : 203-539-1 ; CAS No. : 107-98-2
Weight fraction : $< 2,5$ %
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : A-Clean 518
Revision date : 06-07-2016
Print date : 30-04-2018

Version (Revision) : 5

When in doubt or if symptoms are observed, get medical advice.

Following inhalation

No special measures are necessary.

In case of skin contact

Wash immediately with: Water and soap Change contaminated, saturated clothing. Wash contaminated clothing prior to re-use.

After eye contact

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Call a physician in any case! Do NOT induce vomiting. If major quantity of dust is swallowed or inhaled, immediately drink: Water

4.2 Most important symptoms and effects, both acute and delayed

The following symptoms may occur: No known symptoms to date. Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water mist Foam Extinguishing powder Carbon dioxide (CO₂)

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Do not breathe gas/fumes/vapour/spray. Carbon monoxide Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Protective clothing.

5.4 Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment

Avoid contact with skin, eyes and clothes. Use personal protection equipment.

Emergency procedures

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Make sure spills can be contained, e.g. in sump pallets or kerbed areas. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

For containment

Collect in closed and suitable containers for disposal. Treat the recovered material as prescribed in the section on waste disposal.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : A-Clean 518
Revision date : 06-07-2016
Print date : 30-04-2018

Version (Revision) : 5

For cleaning up

Suitable material for taking up: Sand Absorbing material, organic

6.4 Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage



7.1 Precautions for safe handling

None

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep/Store only in original container. Suitable container/equipment material: Stainless steel Polyethylene (PE)

Unsuitable container/equipment material: Butyl caoutchouc (butyl rubber)

Hints on joint storage

Storage class : 8B

Storage class (TRGS 510) : 8B

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

PHOSPHORIC ACID ; CAS No. : 7664-38-2

Limit value type (country of origin) : TRGS 900 (D)

Parameter : E: inhalable fraction

Limit value : 2 mg/m³

Peak limitation : 2(I)

Remark : Y

Version : 04-11-2017

Limit value type (country of origin) : STEL (EC)

Limit value : 2 mg/m³

Version : 08-06-2000

Limit value type (country of origin) : TWA (EC)

Limit value : 1 mg/m³

Version : 08-06-2000

AMMONIUM BIFLUORIDE ; CAS No. : 1341-49-7

Limit value type (country of origin) : TRGS 900 (D)

Parameter : E: inhalable fraction

Limit value : 2,5 mg/m³

Peak limitation : 2(II)

Version : 04-11-2017

Limit value type (country of origin) : TWA (EC)

Limit value : 2,5 mg/m³

Version : 08-06-2000

1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2

Limit value type (country of origin) : TRGS 900 (D)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : A-Clean 518
Revision date : 06-07-2016
Print date : 30-04-2018

Version (Revision) : 5

Limit value : 100 ppm / 370 mg/m³
Peak limitation : 2(I)
Remark : Y
Version : 04-11-2017
Limit value type (country of origin) : STEL (EC)
Limit value : 150 ppm / 568 mg/m³
Remark : H
Version : 08-06-2000
Limit value type (country of origin) : TWA (EC)
Limit value : 100 ppm / 375 mg/m³
Remark : H
Version : 08-06-2000

Biological limit values

AMMONIUM BIFLUORIDE ; CAS No. : 1341-49-7

Limit value type (country of origin) : TRGS 903 (D)
Parameter : Fluoride / Urine (U) / End of exposure or end of shift
Limit value : 7 mg/g Kr
Version : 31-03-2004
Limit value type (country of origin) : TRGS 903 (D)
Parameter : Fluoride / Urine (U) / Before next shift
Limit value : 4 mg/g Kr
Version : 31-03-2004

8.2 Exposure controls

Personal protection equipment



Eye/face protection

Eye glasses with side protection

Skin protection

Hand protection Suitable gloves type DIN EN 374 Butyl caoutchouc (butyl rubber) NBR (Nitrile rubber) Required properties liquid-tight. Breakthrough time (maximum wearing time) Permeation time (maximum wear time) Thickness of the glove material Nitril: 0,12 mm Butyl: 0,50 mm

General health and safety measures

Immediately remove any contaminated clothing, shoes or stockings. Wash contaminated clothing prior to re-use.

Environmental exposure controls

See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Colour : light yellow

Odour : characteristic

Safety relevant basis data

Physical state :			liquid
Melting point/melting range :			No data available
Initial boiling point and boiling range :	(1013 hPa)	>	100 °C
Decomposition temperature :		>	200 °C
Freezing point :			No data available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : A-Clean 518
Revision date : 06-07-2016
Print date : 30-04-2018

Version (Revision) : 5

Flash point :				not applicable
Auto-ignition temperature :				not applicable
Lower explosion limit :				not applicable
Upper explosion limit :				not applicable
Vapour Pressure :	(20 °C)			No data available
Evaporation rate (n-butylacetate = 1) :				No data available
Density :	(20 °C)	approx.	1,14	g/cm ³
Water solubility :	(20 °C)		100	Wt %
pH :			2,5	
Partition coefficient (n-octanol/water) :		<	3	
Viscosity :	(20 °C)	<	10	mPa.s
Vapour density (air = 1) :	(101 kPa)			No data available
Valt onder Detergentia Verordening (EG) Nr. 648/2004 J/N				yes
anionic surfactants			18,4	%

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

not applicable

10.2 Chemical stability

Stable under normal conditions of use

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

Strong oxidizers

10.6 Hazardous decomposition products

No information available.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute effects

Acute oral toxicity

Parameter :	LD50 (PHOSPHORIC ACID ; CAS No. : 7664-38-2)
Exposure route :	Oral
Species :	Rat
Effective dose :	1530 mg/kg
Parameter :	LD50 (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Exposure route :	Oral
Species :	Rat
Effective dose :	5660 mg/kg

Acute dermal toxicity

Parameter :	LD50 (PHOSPHORIC ACID ; CAS No. : 7664-38-2)
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	2740 mg/kg

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : A-Clean 518
Revision date : 06-07-2016
Print date : 30-04-2018

Version (Revision) : 5

Parameter : LD50 (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Exposure route : Dermal
Species : Rabbit
Effective dose : 9999,99 mg/kg

Irritant and corrosive effects

Primary irritation to the skin

Irritant.

Irritation to eyes

Irritant.

Irritation to respiratory tract

No data available

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

This substance does not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Germ cell mutagenicity

No indications of human germ cell mutagenicity exist.

Reproductive toxicity

This substance does not meet the criteria for classification as CMR category 1A or 1B according to CLP.

STOT-single exposure

not applicable

STOT-repeated exposure

Prolonged or repeated contact with skin or mucous membrane result in irritation symptoms such as redness, blistering, dermatitis, etc.

SECTION 12: Ecological information

12.1 Toxicity

harmless to aquatic organisms up to the tested concentration

12.2 Persistence and degradability

Biodegradable.

12.3 Bioaccumulative potential

No indication of bioaccumulation potential.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.6 Other adverse effects

None

12.7 Additional ecotoxicological information

None

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Delivery to an approved waste disposal company. Contaminated packages must be completely emptied and can be re-used following proper cleaning. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

14.1 UN number

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : A-Clean 518
Revision date : 06-07-2016
Print date : 30-04-2018

Version (Revision) : 5

UN 3264

14.2 UN proper shipping name

Land transport (ADR/RID)

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (ALKYLBEENZEENSULFONZUUR · AMMONIUM BIFLUORIDE)

Sea transport (IMDG)

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (ALKYLBEENZEENSULFONZUUR · AMMONIUM BIFLUORIDE)

Air transport (ICAO-TI / IATA-DGR)

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (ALKYLBEENZEENSULFONZUUR · AMMONIUM BIFLUORIDE)

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 8
Classification code : C1
Hazard identification number (Kemler No.) : 80
Tunnel restriction code : E
Special provisions : LQ 1 | · E 2
Hazard label(s) :



8

Sea transport (IMDG)

Class(es) : 8
EmS-No. : F-A / S-B
Special provisions : LQ 1 | · E 2 · Segregation Group 1 - Acids
Hazard label(s) :



8

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 8
Special provisions : E 2
Hazard label(s) :



8

14.4 Packing group

II

14.5 Environmental hazards

Land transport (ADR/RID) : No

Sea transport (IMDG) : No

Air transport (ICAO-TI / IATA-DGR) : No

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : A-Clean 518
Revision date : 06-07-2016
Print date : 30-04-2018

Version (Revision) : 5

Other regulations (EU)

Labelling for contents according to regulation (EC) No. 648/2004

anionic surfactants 15 - < 30 %

National regulations

Technische Anleitung Luft (TA-Luft)

Weight fraction (Number 5.2.2. III) : 3 - 4 %

Water hazard class (WGK)

Class : 1 (Slightly hazardous to water) Classification according to VwVwS

15.2 Chemical safety assessment

Chemical safety assessments for substances in this preparation were not carried out.

SECTION 16: Other information

16.1 Indication of changes

02. Label elements · 03. Hazardous ingredients

16.2 Abbreviations and acronyms

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road

ASTM = American Society of Testing and Materials (US)

CAS No = Chemical Abstracts Service Number (see ACS - American Chemical Society)

DNEL = Derived No-Effect Level

DT50 = Time for 50% loss; half-life

EbC50 = Median effective concentration (biomass, e.g. of algae)

EC50 = Median effective concentration

EINECS = European Inventory of Existing Commercial Chemical Substances

ELINCS = European List of Notified (New) Chemicals (see Tab 7, Background - Guide)

ErC50 = Median effective concentration (growth rate, e.g. of algae)

EWC = European Waste Catalogue

IATA = International Air Transport Association

IC50 = Concentration that produces 50% inhibition

IMDG = International Maritime Dangerous Goods Code

IMO = International Maritime Organization

LC50 = Concentration required to kill 50% of test organisms

LD50 = Dose required to kill 50% of test organisms

LEL = Lower Explosive Limit/Lower Explosion Limit

LOAEL = Lowest observed adverse effect level

MRL = Maximum Residue Limit

NOAEL = No Observed Adverse Effect Level

NOEC = No observed effect concentration

NOEL = No Observable Effect Level

OEL = Occupational Exposure Limits

PBT = Persistent, Bioaccumulative or Toxic

PNEC = Previsible Non Effect Concentration

STEL = Short-Term Exposure Limit

TWA = Time-Weighted Average

vPvB = Very Persistent and Very Bioaccumulative

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H302	Harmful if swallowed.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : A-Clean 518
Revision date : 06-07-2016
Print date : 30-04-2018

Version (Revision) : 5

H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

16.6 Training advice

None

16.7 Additional information

Article No.: 500633041020

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
